

04-24-00

A

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Inventorship.....Jiang et al.
 Applicant..... Microsoft Corporation
 Attorney's Docket No. MS1-442US
 Title: Improved Audio Segmentation and Classification

TRANSMITTAL LETTER AND CERTIFICATE OF MAILING

To: Commissioner of Patents and Trademarks
 Washington, D.C. 20231

From: Allan T. Sponseller (509) 324-9256
 Lee & Hayes, PLLC
 421 W. Riverside Avenue, Suite 500
 Spokane, WA 99201

The following enumerated items accompany this transmittal letter and are being submitted for the matter identified in the above caption.

1. Transmittal Letter with Certificate of Mailing included.
2. PTO Return Postcard Receipt
3. Check in the Amount of \$1,660.00
4. Fee Transmittal
5. New patent application (title page plus 40 pages, including claims 1-50 & Abstract)
6. Executed Declaration
7. 5 sheets of formal drawings (Figs. 1-5)
8. Assignment w/Recordation Cover Sheet

Large Entity Status ☒

Small Entity Status ☐

The Commissioner is hereby authorized to charge payment of fees or credit overpayments to Deposit Account No. 12-0769 in connection with any patent application filing fees under 37 CFR 1.16, and any processing fees under 37 CFR 1.17.

Date: April 17, 2000

By: [Signature]
 Allan T. Sponseller
 Reg. No. 38,318

CERTIFICATE OF MAILING

I hereby certify that the items listed above as enclosed are being deposited with the U.S. Postal Service as either first class mail, or Express Mail if the blank for Express Mail No. is completed below, in an envelope addressed to The Commissioner of Patents and Trademarks, Washington, D.C. 20231, on the below-indicated date. Any Express Mail No. has also been marked on the listed items.

Express Mail No. (if applicable) EL5 80803909

Date: 4.19.00

By: [Signature]
 Lori A. Vierra

04/19/00



04/19/00

jc542 U.S. PTO

09/553166



04/19/00

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION FOR LETTERS PATENT

Improved Audio Segmentation and Classification

Inventor(s):

Hao Jiang

Hongjiang Zhang

ATTORNEY'S DOCKET NO. MS1-442US

TECHNICAL FIELD

This invention relates to audio information retrieval, and more particularly to segmenting and classifying audio.

BACKGROUND OF THE INVENTION

Computer technology is continually advancing, providing computers with continually increasing capabilities. One such increased capability is audio information retrieval. Audio information retrieval refers to the retrieval of information from an audio signal. This information can be the underlying content of the audio signal (e.g., the words being spoken), or information inherent in the audio signal (e.g., when the audio has changed from a spoken introduction to music).

One fundamental aspect of audio information retrieval is classification. Classification refers to placing the audio signal (or portions of the audio signal) into particular categories. There is a broad range of categories or classifications that would be beneficial in audio information retrieval, including speech, music, environment sound, and silence. Currently, techniques classify audio signals as speech or music, and either do not allow for classification of audio signals as environment sound or silence, or perform such classifications poorly (e.g., with a high degree of inaccuracy).

Additionally, when the audio signal represents speech, separating the audio signal into different segments corresponding to different speakers could be beneficial in audio information retrieval. For example, a separate notification (such as a visual notification) could be given to a user to inform the user that the speaker has changed. Current classification techniques either do not allow for

1 identifying speaker changes or identify speaker changes poorly (e.g., with a high
2 degree of inaccuracy).

3 The improved audio segmentation and classification described below
4 addresses these disadvantages, providing improved segmentation and
5 classification of audio signals.

6 7 **SUMMARY OF THE INVENTION**

8 Improved audio segmentation and classification is described herein. A
9 portion of an audio signal is separated into multiple frames from which one or
10 more different features are extracted. These different features are used to classify
11 the portion of the audio signal into one of multiple different classifications (for
12 example, speech, non-speech, music, environment sound, silence, etc.).

13 According to one aspect, line spectrum pairs (LSPs) are extracted from
14 each of the multiple frames. These LSPs are used to generate an input Gaussian
15 Model representing the portion. The input Gaussian Model is compared to a
16 codebook of trained Gaussian Model and the distance between the input Gaussian
17 Model and the closest trained Gaussian Model is determined. This distance is then
18 used, optionally in combination with an energy distribution of the multiple frames
19 in one or more bandwidths, to determine whether to classify the portion as speech
20 or non-speech.

21 According to another aspect, one or more periodicity features are extracted
22 from each of the multiple frames. These periodicity features include, for example,
23 a noise frame ratio indicating a ratio of noise-like frames in the portion, and
24 multiple band periodicities, each indicating a periodicity in a particular frequency
25 band of the portion. A full band periodicity may also be determined, which is a

combination (e.g., a concatenation) of each of the multiple individual band periodicities. These periodicity features are then used, individually or in combination, to discriminate between music and environment sound. Other features may also optionally be used to determine whether the portion is music or environment sound, including spectrum flux features and energy distribution in one or more of the multiple bands (either the same bands as were used for the band periodicities, or different bands).

According to another aspect, the audio signal is also segmented. The segmentation identifies when the audio classification changes as well as when the current speaker changes (when the audio signal is speech). Line spectrum pairs extracted from the portion of the audio signal are used to determine when the speaker changes. In one implementation, when the difference between line spectrum pairs for two frames (or alternatively windows of multiple frames) is a local peak and exceeds a threshold value, then a speaker change is identified as occurring between those two frames (or windows).

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention is illustrated by way of example and not limitation in the figures of the accompanying drawings. The same numbers are used throughout the figures to reference like components and/or features.

Fig. 1 is a block diagram illustrating an exemplary system for classifying and segmenting audio signals.

Fig. 2 shows a general example of a computer that can be used in accordance with one embodiment of the invention.

1 Fig. 3 is a more detailed block diagram illustrating an exemplary system for
2 classifying and segmenting audio signals.

3 Fig. 4 is a flowchart illustrating an exemplary process for discriminating
4 between speech and non-speech in accordance with one embodiment of the
5 invention.

6 Fig. 5 is a flowchart illustrating an exemplary process for classifying a
7 portion of an audio signal as speech, music, environment sound, or silence in
8 accordance with one embodiment of the invention.

9 10 **DETAILED DESCRIPTION**

11 In the discussion below, embodiments of the invention will be described in
12 the general context of computer-executable instructions, such as program modules,
13 being executed by one or more conventional personal computers. Generally,
14 program modules include routines, programs, objects, components, data structures,
15 etc. that perform particular tasks or implement particular abstract data types.
16 Moreover, those skilled in the art will appreciate that various embodiments of the
17 invention may be practiced with other computer system configurations, including
18 hand-held devices, multiprocessor systems, microprocessor-based or
19 programmable consumer electronics, network PCs, minicomputers, mainframe
20 computers, and the like. In a distributed computer environment, program modules
21 may be located in both local and remote memory storage devices.

22 Alternatively, embodiments of the invention can be implemented in
23 hardware or a combination of hardware, software, and/or firmware. For example,
24 one implementation of the invention can include one or more application specific
25 integrated circuits (ASICs).

1 In the discussions herein, reference is made to many different specific
2 numerical values (e.g., frequency bands, threshold values, etc.). These specific
3 values are exemplary only – those skilled in the art will appreciate that different
4 values could alternatively be used.

5 Additionally, the discussions herein and corresponding drawings refer to
6 different devices or components as being coupled to one another. It is to be
7 appreciated that such couplings are designed to allow communication among the
8 coupled devices or components, and the exact nature of such couplings is
9 dependent on the nature of the corresponding devices or components.

10 Fig. 1 is a block diagram illustrating an exemplary system for classifying
11 and segmenting audio signals. A system 102 is illustrated including an audio
12 analyzer 104. System 102 represents any of a wide variety of computing devices,
13 including set-top boxes, gaming consoles, personal computers, etc. Although
14 illustrated as a single component, analyzer 104 may be implemented as multiple
15 programs. Additionally, part or all of the functionality of analyzer 104 may be
16 incorporated into another program, such as an operating system, an Internet
17 browser, etc.

18 Audio analyzer 104 receives an input audio signal 106. Audio signal 106
19 can be received from any of a wide variety of sources, including audio broadcasts
20 (e.g., analog or digital television broadcasts, satellite or RF radio broadcasts, audio
21 streaming via the Internet, etc.), databases (either local or remote) of audio data,
22 audio capture devices such as microphones or other recording devices, etc.

23 Audio analyzer 104 analyzes input audio signal 106 and outputs both
24 classification information 108 and segmentation information 110. Classification
25 information 108 identifies, for different portions of audio signal 106, which one of

multiple different classifications the portion is assigned. In the illustrated example, these classifications include one or more of the following: speech, non-speech, silence, environment sound, music, music with vocals, and music without vocals.

Segmentation information 110 identifies different segments of audio signal 106. In the case of portions of audio signal 106 classified as speech, segmentation information 110 identifies when the speaker of audio signal 106 changes. In the case of portions of audio signal 106 that are not classified as speech, segmentation information 110 identifies when the classification of audio signal 106 changes.

In the illustrated example, analyzer 104 analyzes the portions of audio signal 106 as they are received and outputs the appropriate classification and segmentation information while subsequent portions are being received and analyzed. Alternatively, analyzer 104 may wait until larger groups of portions have been received (or all of audio signal 106) prior to performing its analyzing.

Fig. 2 shows a general example of a computer 142 that can be used in accordance with one embodiment of the invention. Computer 142 is shown as an example of a computer that can perform the functions of system 102 of Fig. 1. Computer 142 includes one or more processors or processing units 144, a system memory 146, and a bus 148 that couples various system components including the system memory 146 to processors 144.

The bus 148 represents one or more of any of several types of bus structures, including a memory bus or memory controller, a peripheral bus, an accelerated graphics port, and a processor or local bus using any of a variety of bus architectures. The system memory includes read only memory (ROM) 150 and random access memory (RAM) 152. A basic input/output system (BIOS) 154,

1 containing the basic routines that help to transfer information between elements
2 within computer 142, such as during start-up, is stored in ROM 150. Computer
3 142 further includes a hard disk drive 156 for reading from and writing to a hard
4 disk, not shown, connected to bus 148 via a hard disk driver interface 157 (e.g., a
5 SCSI, ATA, or other type of interface); a magnetic disk drive 158 for reading from
6 and writing to a removable magnetic disk 160, connected to bus 148 via a
7 magnetic disk drive interface 161; and an optical disk drive 162 for reading from
8 or writing to a removable optical disk 164 such as a CD ROM, DVD, or other
9 optical media, connected to bus 148 via an optical drive interface 165. The drives
10 and their associated computer-readable media provide nonvolatile storage of
11 computer readable instructions, data structures, program modules and other data
12 for computer 142. Although the exemplary environment described herein employs
13 a hard disk, a removable magnetic disk 160 and a removable optical disk 164, it
14 should be appreciated by those skilled in the art that other types of computer
15 readable media which can store data that is accessible by a computer, such as
16 magnetic cassettes, flash memory cards, digital video disks, random access
17 memories (RAMs) read only memories (ROM), and the like, may also be used in
18 the exemplary operating environment.

19 A number of program modules may be stored on the hard disk, magnetic
20 disk 160, optical disk 164, ROM 150, or RAM 152, including an operating system
21 170, one or more application programs 172, other program modules 174, and
22 program data 176. A user may enter commands and information into computer
23 142 through input devices such as keyboard 178 and pointing device 180. Other
24 input devices (not shown) may include a microphone, joystick, game pad, satellite
25 dish, scanner, or the like. These and other input devices are connected to the

1 processing unit 144 through an interface 182 that is coupled to the system bus. A
2 monitor 184 or other type of display device is also connected to the system bus
3 148 via an interface, such as a video adapter 186. In addition to the monitor,
4 personal computers typically include other peripheral output devices (not shown)
5 such as speakers and printers.

6 Computer 142 can optionally operate in a networked environment using
7 logical connections to one or more remote computers, such as a remote computer
8 188. The remote computer 188 may be another personal computer, a server, a
9 router, a network PC, a peer device or other common network node, and typically
10 includes many or all of the elements described above relative to computer 142,
11 although only a memory storage device 190 has been illustrated in Fig. 2. The
12 logical connections depicted in Fig. 2 include a local area network (LAN) 192 and
13 a wide area network (WAN) 194. Such networking environments are
14 commonplace in offices, enterprise-wide computer networks, intranets, and the
15 Internet. In the described embodiment of the invention, remote computer 188
16 executes an Internet Web browser program such as the "Internet Explorer" Web
17 browser manufactured and distributed by Microsoft Corporation of Redmond,
18 Washington.

19 When used in a LAN networking environment, computer 142 is connected
20 to the local network 192 through a network interface or adapter 196. When used
21 in a WAN networking environment, computer 142 typically includes a modem 198
22 or other means for establishing communications over the wide area network 194,
23 such as the Internet. The modem 198, which may be internal or external, is
24 connected to the system bus 148 via a serial port interface 168. In a networked
25 environment, program modules depicted relative to the personal computer 142, or

1 portions thereof, may be stored in the remote memory storage device. It will be
2 appreciated that the network connections shown are exemplary and other means of
3 establishing a communications link between the computers may be used.

4 Computer 142 can also optionally include one or more broadcast tuners
5 200. Broadcast tuner 200 receives broadcast signals either directly (e.g., analog or
6 digital cable transmissions fed directly into tuner 200) or via a reception device
7 (e.g., via an antenna or satellite dish (not shown)).

8 Generally, the data processors of computer 142 are programmed by means
9 of instructions stored at different times in the various computer-readable storage
10 media of the computer. Programs and operating systems are typically distributed,
11 for example, on floppy disks or CD-ROMs. From there, they are installed or
12 loaded into the secondary memory of a computer. At execution, they are loaded at
13 least partially into the computer's primary electronic memory. The invention
14 described herein includes these and other various types of computer-readable
15 storage media when such media contain instructions or programs for implementing
16 the steps described below in conjunction with a microprocessor or other data
17 processor. The invention also includes the computer itself when programmed
18 according to the methods and techniques described below. Furthermore, certain
19 sub-components of the computer may be programmed to perform the functions
20 and steps described below. The invention includes such sub-components when
21 they are programmed as described. In addition, the invention described herein
22 includes data structures, described below, as embodied on various types of
23 memory media.

24 For purposes of illustration, programs and other executable program
25 components such as the operating system are illustrated herein as discrete blocks,

1 although it is recognized that such programs and components reside at various
2 times in different storage components of the computer, and are executed by the
3 data processor(s) of the computer.

4 Fig. 3 is a more detailed block diagram illustrating an exemplary system for
5 classifying and segmenting audio signals. System 102 includes a buffer 212 that
6 receives a digital audio signal 214. Audio signal 214 can be received at system
7 102 in digital form or alternatively can be received at system 102 in analog form
8 and converted to digital form by a conventional analog to digital (A/D) converter
9 (not shown). In one implementation, buffer 212 stores at least one second of audio
10 signal 214, which system 102 will classify as discussed in more detail below.
11 Alternatively, buffer 212 may store different amounts of audio signal 214.

12 In the illustrated example, the digital audio signal 214 is sampled at 32KHz
13 per second. In the event that the source of audio signal 214 has sampled the audio
14 signal at a higher rate, it is down sampled by system 102 (or alternatively another
15 component) to 32KHz for classification and segmentation.

16 Buffer 212 forwards a portion (e.g., one second) of signal 214 to framer
17 216, which in turn separates the portion of signal 214 into multiple non-
18 overlapping sub-portions, referred to as "frames". In one implementation, each
19 frame is a 25 millisecond (ms) sub-portion of the received portion of signal 214.
20 Thus, by way of example, if the buffered portion of signal 214 is one second of
21 audio signal 214, then framer 216 separates the portion into 40 different 25ms
22 frames.

23 The frames generated by framer 216 are input to a Line Spectrum Pair
24 (LSP) analyzer 218, K-Nearest Neighbor (KNN) analyzer 220, Fast Fourier
25 Transform (FFT) analyzer 222, spectrum flux analyzer 224, bandpass (BP) filter

226, and correlation analyzer 228. These analyzers and filter 218 – 228 extract various features of signal 214 from each frame. The use of such extracted features for classification and segmentation is discussed in more detail below. As illustrated, the frames of signal 214 are input to analyzers and filter 218 – 228 for concurrent processing by analyzers and filter 218 – 228. Alternatively, such processing may occur sequentially, or may only occur when needed (e.g., non-speech features may not be extracted if the portion of signal 214 is classified as speech).

LSP analyzer 218 extracts Line Spectrum Pairs (LSPs) for each frame received from framer 216. Speech can be described using the well-known vocal channel excitation model. The vocal channel in people (and many animals) forms a resonant system which introduces formant structure to the envelope of speech spectrum. This structure is described using linear prediction (LP) coefficients. In one implementation, the LP coefficients are 10-order coefficients (i.e., 10-Dim vectors). The LP coefficients are then converted to LSPs. The calculation of LP coefficients and extraction of Line Spectrum Pairs from the LP coefficients are well known to those skilled in the art and thus will not be discussed further except as they pertain to the invention.

The extracted LSPs are input to a speech class vector quantization (VQ) distance calculator 230. Distance calculator 230 accesses a codebook 232 which includes trained Gaussian Models (GMs) used in classifying portions of audio signal 214 as speech or non-speech. Codebook 232 is generated using training speech data in any of a wide variety of manners, such as by using the LBG (Linde-Buzo-Gray) algorithm or K-Means Clustering algorithm. Gaussian Models are generated in a conventional manner from training speech data, which can include

speech by different speakers, speakers of different ages and/or sexes, different conditions (e.g., different background noises), etc. A number of these Gaussian Models that are similar to one another are grouped together using conventional VQ clustering. A single "trained" Gaussian Model is then selected from each group (e.g., the model that is at approximately the center of a group, a randomly selected model, etc.) and is used as a vector in the training set, resulting in a training set of vectors (or "trained" Gaussian Models). The trained Gaussian Models are stored in codebook 232. In one implementation, codebook 232 includes four trained Gaussian Models. Alternatively, different numbers of code vectors may be included in codebook 232.

It should be noted that, contrary to traditional VQ classification techniques, only a single codebook 232 for the trained speech data is generated. An additional codebook for non-speech data is not necessary.

Distance calculator 230 also generates an input GM in a conventional manner based on the extracted LSPs for the frames in the portion of signal 214 to be classified. Alternatively, LSP analyzer 218 may generate the input GM rather than calculator 230. Regardless of which component generates the input GM, the distance between the input GM and the closest trained GM in codebook 232 is determined. The closest trained GM in codebook 232 can be identified in any of a variety of manners, such as calculating the distance between the input GM and each trained GM in codebook 232, and selecting the smallest distance.

The distance between the input GM and a trained GM can be calculated in a variety of conventional manners. In one implementation, the distance is generated according to the following calculation:

$$D(X, Y) = \text{tr}[(C_X - C_Y)(C_Y^{-1} - C_X^{-1})]$$

1 where $D(X,Y)$ represents the distance between a Gaussian Model X and another
2 Gaussian Model Y , C_X represents the covariance matrix of Gaussian Model X , C_Y
3 represents the covariance matrix of Gaussian Model Y , and C^{-1} represents the
4 inverse of a covariance matrix.

5 Although discussed with reference to Gaussian Models, other models can
6 also be used for discriminating between speech and non-speech. For example,
7 conventional Gaussian Mixture Models (GMMs) could be used, Hidden Markov
8 Models (HMMs) could be used, etc.

9 Calculator 230 then inputs the calculated distance to speech discriminator
10 234. Speech discriminator 234 uses the distance it receives from calculator 230 to
11 classify the portion of signal 214 as speech or non-speech. If the distance is less
12 than a threshold value (e.g., 20) then the portion of signal 214 is classified as
13 speech; otherwise, it is classified as non-speech.

14 The speech/non-speech classification made by speech discriminator 234 is
15 output to audio segmentation and classification integrator 236. Integrator 236 uses
16 the speech/non-speech classification, possibly in conjunction with additional
17 information received from other components, to determine the appropriate
18 classification and segmentation information to output as discussed in more detail
19 below.

20 Speech discriminator 234 may also optionally output an indication of its
21 speech/non-speech classification to other components, such as filter 226 and
22 analyzer 228. Filter 226 and analyzer 228 extract features that are used in
23 discriminating among music, environment sound, and silence. If a portion of
24 audio signal 214 is speech then the features extracted by filter 226 and analyzer
25 228 are not needed. Thus, the indication from speech discriminator 234 can be

1 used to inform filter 226 and analyzer 228 that they need not extract features for
2 that portion of audio signal 214.

3 In one implementation, speech discriminator 234 performs its classification
4 based solely on the distance received from calculator 230. In alternative
5 implementations, speech discriminator 234 relies on other information received
6 from KNN analyzer 220 and/or FFT analyzer 222.

7 KNN analyzer 220 extracts two time domain features from each frame of a
8 portion of audio signal 214: a high zero crossing rate ratio and a low short time
9 energy ratio. The high zero crossing rate ratio refers to the ratio of frames with
10 zero crossing rates higher than the 150% average zero crossing rate in one portion.
11 The low short time energy ratio refers to the ratio of frames with short time energy
12 lower than the 50% average short time energy in the portion. Spectrum flux is
13 another feature used in KNN classification, which can be obtained by spectrum
14 flux analyzer 224 as discussed in more detail below. The extraction of zero
15 crossing rate and short time energy features from a digital audio signal is well
16 known to those skilled in the art and thus will not be discussed further except as it
17 pertains to the invention.

18 KNN analyzer 220 generates two codebooks (one for speech and one for
19 non-speech) based on training data. This can be the same training data used to
20 generate codebook 232 or alternatively different training data. KNN analyzer 220
21 then generates a set of feature vectors based on the low short time energy ratio, the
22 high zero crossing rate ratio, and the spectrum flux (e.g., by concatenating these
23 three values) of the training data. An input signal feature vector is also extracted
24 from each portion of audio signal 214 (based on the low short time energy ratio,
25 the high zero crossing rate ratio, and the spectrum flux) and compared with the

1 feature vectors in each of the codebooks. Analyzer 220 then identifies the nearest
2 K vectors, considering vectors in both the speech and non-speech codebooks (K is
3 typically selected as an odd number, such as 3 or 5).

4 Speech discriminator 234 uses the information received from KNN
5 classifier 220 to pre-classify the portion as speech or non-speech. If there are
6 more vectors among the K nearest vectors from the speech codebook than from
7 the non-speech codebook, then the portion is pre-classified as speech. However, if
8 there are more vectors among the K nearest vectors from the non-speech codebook
9 than from the speech codebook, then the portion is pre-classified as non-speech.
10 Speech discriminator 234 then uses the result of the pre-classification to determine
11 a distance threshold to apply to the distance information received from speech
12 class VQ distance calculator 230. Speech discriminator 234 applies a higher
13 threshold if the portion is pre-classified as non-speech than if the portion is pre-
14 classified as speech. In one implementation, speech discriminator 234 uses a zero
15 decibel (dB) threshold if the portion is pre-classified as speech, and uses a 6 dB
16 threshold if the portion is pre-classified as non-speech.

17 Alternatively, speech discriminator 234 may utilize energy distribution
18 features of the portion of audio signal 214 in determining whether to classify the
19 portion as speech. FFT analyzer 222 extracts FFT features from each frame of a
20 portion of audio signal 214. The extraction of FFT features from a digital audio
21 signal is well known to those skilled in the art and thus will not be discussed
22 further except as it pertains to the invention. The extracted FFT features are input
23 to energy distribution calculator 238. Energy distribution calculator 238
24 calculates, based on the FFT features, the energy distribution of the portion of the
25 audio signal 214 in each of two different bands. In one implementation, the first

1 of these bands is 0 to 4,000 Hz (the 4kHz band) and the second is 0 to 8,000 Hz
2 (the 8kHz band). The energy distribution in each of these bands is then input to
3 speech discriminator 234.

4 Speech discriminator 234 determines, based on the distance information
5 received from distance calculator 230 and/or the energy distribution in the bands
6 received from energy distribution calculator 238, whether the portion of audio
7 signal 214 is to be classified as speech or non-speech.

8 Fig. 4 is a flowchart illustrating an exemplary process for discriminating
9 between speech and non-speech in accordance with one embodiment of the
10 invention. The process of Fig. 4 is implemented by calculators 230 and 238, and
11 speech discriminator 234 of Fig. 3, and may be performed in software. Fig. 4 is
12 described with additional reference to components in Fig. 3.

13 Initially, energy distribution calculator 236 determines the energy
14 distribution of the portion of signal 214 in the 4kHz and 8kHz bands (act 240) and
15 speech to class VQ distance calculator 230 determines the distance from the input
16 GM (corresponding to the portion of signal 214 being classified) and the closest
17 trained GM (act 242).

18 Speech discriminator 234 then checks whether the distance determined in
19 act 242 is greater than 30 (act 244). If the distance is greater than 30, then
20 discriminator 234 classifies the portion as non-speech (act 246). However, if the
21 distance is not greater than 30, then discriminator 234 checks whether the distance
22 determined in act 242 is greater than 20 and the energy in the 4kHz band
23 determined in act 240 is less than 0.95 (act 248). If the distance determined is
24 greater than 20 and the energy in the 4kHz band is less than 0.95, then
25 discriminator 234 classifies the portion as non-speech (act 246).

1 However, if distance determined is not greater than 20 and/or the energy in
2 the 4kHz band is not less than 0.95, then discriminator 234 checks whether the
3 distance determined in act 242 is less than 20 and whether the energy in the 8kHz
4 band determined in act 240 is greater than 0.997 (act 250). If the distance is less
5 than 20 and the energy in the 8kHz band is greater than 0.997, then the portion is
6 classified as speech (act 252); otherwise, the portion is classified as non-speech
7 (act 246).

8 Returning to Fig. 3, LSP analyzer 218 also outputs the LSP features to LSP
9 window distance calculator 258. Calculator 258 calculates the distance between
10 the LSPs for successive windows of audio signal 214, buffering the extracted
11 LSPs for successive windows (e.g., for two successive windows) in order to
12 perform such calculations. These calculated distances are then input to audio
13 segmentation and speaker change detector 260. Detector 260 compares the
14 calculated distances to a threshold value (e.g., 4.75) and determines an audio
15 segment boundary exists between two windows if the distance between those two
16 windows exceeds the threshold value. Audio segment boundaries refer to changes
17 in speaker if the analyzed portion(s) of the audio signal are speech, and refers to
18 changes in classification if the analyzed portion(s) of the audio signal include non-
19 speech.

20 In one implementation the size of such a window is three seconds (e.g.,
21 corresponding to 120 consecutive 25ms frames). Alternatively, different window
22 sizes could be used. Increasing the window size increases the accuracy of the
23 audio segment boundary detection, but reduces the time resolution of the boundary
24 detection (e.g., if windows are three seconds, then boundaries can only be detected
25 down to a three-second resolution), thereby increasing the chances of missing a

short audio segment (e.g., less than three seconds). Decreasing the window size increases the time resolution of the boundary detection, but also increases the chances of an incorrect boundary detection.

Calculator 258 generates an LSP feature for a particular window that represents the LSP features of the individual frames in that window. The distance between LSP features of two different frames or windows can be calculated in any of a variety of conventional manners, such as via the well-known likelihood ratio or non-parameter techniques. In one implementation, the distance between two LSP features set X and Y is measured using divergence. Divergence is defined as follows:

$$D = J_{XY} = I(X, Y) + I(Y, X) = \int_x [p_X(\xi) - p_Y(\xi)] \ln \frac{p_X(\xi)}{p_Y(\xi)} d\xi$$

where D represents the distance between two LSP features set X and Y , p_X is the probability density function (pdf) of X , and p_Y is the pdf of Y . The assumption is made that the feature pdfs are well-known n-variant normal populations, as follows:

$$\begin{aligned} p_X(\xi) &\approx N(\mu_X, C_X) \\ p_Y(\xi) &\approx N(\mu_Y, C_Y) \end{aligned}$$

Divergence can then be represented in a compact form:

$$D = J_{XY} = \frac{1}{2} \text{tr}[(C_X - C_Y)(C_Y^{-1} - C_X^{-1})] + \frac{1}{2} \text{tr}[(C_Y^{-1} + C_X^{-1})(\mu_X - \mu_Y)(\mu_X - \mu_Y)^T]$$

where tr is the matrix trace function, C_X represents the covariance matrix of X , C_Y represents the covariance matrix of Y , C^{-1} represents the inverse of a covariance matrix, μ_X represents the mean of X , μ_Y represents the mean of Y , and T represents the operation of matrix transpose. In one implementation, only the beginning part of the compact form is used in determining divergence, as indicated in the following calculation:

$$D = \frac{1}{2} \text{tr}[(C_X - C_Y)(C_Y^{-1} - C_X^{-1})]$$

Audio segment boundaries are then identified based on the distance between the current window and the previous window (D_i), the distance between the previous window and the window before that (D_{i-1}), and the distance between the current window and the next window (D_{i+1}). Detector 260 uses the following calculation to determine whether an audio segment boundary exists:

$$D_{i-1} < D_i \quad \text{and} \quad D_{i+1} < D_i$$

This calculation helps ensure that a local peak exists for detecting the boundary. Additionally, the distance D_i must exceed a threshold value (e.g., 4.75). If the distance D_i does not exceed the threshold value, then an audio segment boundary is not detected.

Detector 260 outputs audio segment boundary indications to integrator 236. Integrator 236 identifies audio segment boundary indications as speaker changes if the audio signal is speech, and identifies audio segment boundary indications as changes in homogeneous non-speech segments if the audio signal is non-speech. Homogeneous segments refer to one or more sequential portions of audio signal 214 that have the same classification.

System 102 also includes spectrum flux analyzer 224, bandpass filter 226, and correlation analyzer 228. Spectrum flux analyzer 224 analyzes the difference between FFTs in successive frames of the portion of audio signal 214 being classified. The FFT features can be extracted by analyzer 224 itself from the frames output by framer 216, or alternatively analyzer 224 can receive the FFT features from FFT analyzer 222. The average difference between successive frames in the portion of audio signal 214 is calculated and output to music, environment sound, and silence discriminator 262. Discriminator 262 uses the

spectrum flux information received from spectrum flux analyzer 224 in classifying the portion of audio signal 214 as music, environment sound, or silence, as discussed in more detail below.

Discriminator 262 also makes use of two periodicity features in classifying the portion of audio signal 214 as music, environment sound, or silence. These periodicity features are referred to as noise frame ratio and band periodicity, and are discussed in more detail below.

Bandpass filter 226 filters particular frequencies from the frames of audio signal 214 and outputs these bands to band periodicity calculator 264. In one implementation, the bands passed to calculator 264 are 500Hz to 1000Hz, 1000Hz to 2000Hz, 2000Hz to 3000Hz, and 3000Hz to 4000Hz. Band periodicity calculator 264 receives these bands and determines the periodicity of the frames in the portion of audio signal 214 for each of these bands. Additionally, once the periodicity of each of these four bands is determined, a "full band" periodicity is calculated by summing the four individual band periodicities.

The band periodicity can be calculated in any of a wide variety of known manners. In one implementation, the band periodicity for one of the four bands is calculated by initially calculating a correlation function for that band. The correlation function is defined as follows:

$$r(m) = \frac{\sum_{n=0}^{N-1} x(n+m)x(n)}{\left[\sum_{n=0}^{N-1} x^2(n) \right]^{1/2} \left[\sum_{n=0}^{N-1} x^2(n+m) \right]^{1/2}}$$

where $x(n)$ is the input signal, N is the window length, and $r(m)$ represents the correlation function of one band of the portion of audio signal 214 being

1 classified. The maximum local peak of the correlation function for each band is
2 then located in a conventional manner.

3 Additionally, the DC-removed full-wave regularity signal is also used for
4 the calculation of correlation coefficient. The DC-full-wave regularity signal is
5 calculated as follows. First, the absolute value of the input signal is calculated and
6 then passed through a digital filter. The transform function of the digital filter is:

$$7 \quad H(z) = \frac{1 - bz^{-1}}{(1 - az^{-1})(1 + a^* z^{-1})}$$

8 The variables a and b can be determined by experiment, a^* is the conjunctive of a .
9 In one implementation, the value of a is $0.97 \cdot \exp(j \cdot 0.1407)$, with j equaling the
10 square root of -1 , and the value of b is 1. Then the correlation function of the DC-
11 removed full-wave regularity is calculated. A constant is removed from the full-
12 wave regularity signal correlation function. In one implementation this constant is
13 the value 0.1. The larger of the maximum local peak of the correlation function of
14 the input signal and its DC-removed full-wave regularity signal is then selected as
15 the measure of periodicity of that band.

16 Correlation analyzer 228 operates in a conventional manner to generate an
17 autocorrelation function for each frame of the portion of audio signal 214. The
18 autocorrelation functions generated by analyzer 228 are input to noise frame ratio
19 calculator 266. Noise frame ratio calculator 266 operates in a conventional
20 manner to generate a noise frame ratio for the portion of audio signal 214,
21 identifying a percentage of the frames that are noise-like.

22 Discriminator 262 also receives the energy distribution information from
23 calculator 238. The energy distribution across the 4kHz and 8kHz bands may be
24
25

1 used by discriminator 262 in classifying the portion of audio signal 214 as music,
2 silence, or environment sound, as discussed in more detail below.

3 Discriminator 262 further uses the full bandwidth energy in determining
4 whether the portion of audio signal 214 is silence. This full bandwidth energy
5 may be received from calculator 238, or alternatively generated by discriminator
6 262 based on FFT features received from FFT analyzer 222 or based on the
7 information received from calculator 238 regarding the energy distribution in the
8 4kHz and 8kHz bands. In one implementation, the energy in the portion of the
9 signal 214 being classified is normalized to a 16-bit signed value, allowing for a
10 maximum energy value of 32,768, and discriminator 262 classifies the portion as
11 silence only if the energy value of the portion is less than 20.

12 Discriminator 262 classifies the portion of audio signal 214 as music,
13 environment sound, or silence based on various features of the portion.
14 Discriminator 262 applies a set of rules to the information it receives and classifies
15 the portion accordingly. One set of rules is illustrated in Table I below. The rules
16 can be applied in the order of their presentation, or alternatively can be applied in
17 different orders.

Table I

Rule	Result
1: Overall energy is less than 20	Silence
2: Noise frame ratio is greater than 0.45 or full band periodicity is less than 2.1 or periodicity in band 500~1000Hz is less than 0.6 or periodicity in band 1000~2000Hz is less than 0.5	Environmental sound
3: Energy distribution in 8kHz band is less than 0.2 and/or spectrum flux is greater than 12 and/or less than 2	Environmental sound
4: Full band periodicity is greater than 3.8	Environmental sound
5: None of rules 1, 2, 3, or 4 is true	Music

System 102 can also optionally classify portions of audio signal 214 which are music as either music with vocals or music without vocals. This classification can be performed by discriminator 262, integrator 238, or an additional component (not shown) of system 102. Discriminating between music with vocals and music without vocals for a portion of audio signal 214 is based on the periodicity of the portion. If the periodicity of any one of the four bands (500Hz to 1000Hz, 1000Hz to 2000Hz, 2000Hz to 3000Hz, or 3000Hz to 4000Hz) falls within a particular range (e.g., is lower than a first threshold and higher than a second threshold), then the portion is classified as music with vocals. If all of the bands are lower than the second threshold, then the portion is classified as environment sound; otherwise, the portion is classified as music without vocals. In one implementation, the exact values of these two thresholds are determined experimentally.

Fig. 5 is a flowchart illustrating an exemplary process for classifying a portion of an audio signal as speech, music, environment sound, or silence in

1 accordance with one embodiment of the invention. The process of Fig. 5 is
2 implemented by system 102 of Fig. 3, and may be performed in software. Fig. 5 is
3 described with additional reference to components in Fig. 3.

4 A portion of an audio signal is initially received and buffered (act 302).
5 Multiple frames for a portion of the audio signal are then generated (act 304).
6 Various features are extracted from the frames (act 306) and speech/non-speech
7 discrimination is performed using at least a subset of the extracted features (act
8 308).

9 If the portion is speech (act 310), then a corresponding classification (i.e.,
10 speech) is output (act 312). Additionally, a check is made as to whether the
11 speaker has changed (act 314). If the speaker has not changed, then the process
12 returns to continue processing additional portions of the audio signal (act 302).
13 However, if the speaker has changed, then a set of speaker change boundaries are
14 output (act 316). In some implementations, multiple speaker changes may be
15 detectable within a single portion, thereby allowing the set to identify multiple
16 speaker change boundaries for a single portion. In alternative implementations,
17 only a single speaker change may be detectable within a single portion, thereby
18 limiting the set to identify a single speaker change boundary for a single portion.
19 The process then returns to continue processing additional portions of the audio
20 signal (act 302).

21 Returning to act 310, if the portion is not speech then a determination is
22 made as to whether the portion is silence (act 318). If the portion is silence, then a
23 corresponding classification (i.e., silence) is output (act 320). The process then
24 returns to continue processing additional portions of the audio signal (act 302).
25 However, if the portion is not silence then music/environment sound

1 discrimination is performed using at least a subset of the features extracted in act
2 306. The corresponding classification (i.e., music or environment sound) is then
3 output (act 320), and the process returns to continue processing additional portions
4 of the audio signal (act 302).

6 **Conclusion**

7 Thus, improved audio segmentation and classification has been described.
8 Audio segments with different speakers and different classifications can
9 advantageously be identified. Additionally, portions of the audio can be classified
10 as one of multiple different classes (for example, speech, silence, music, or
11 environment sound). Furthermore, classification accuracy between some classes
12 can be advantageously improved by using periodicity features of the audio signal.

13 Although the description above uses language that is specific to structural
14 features and/or methodological acts, it is to be understood that the invention
15 defined in the appended claims is not limited to the specific features or acts
16 described. Rather, the specific features and acts are disclosed as exemplary forms
17 of implementing the invention.

CLAIMS

1. A method comprising:

separating at least a portion of an audio signal into a plurality of frames;

extracting line spectrum pairs from each of the plurality of frames; and

using at least the line spectrum pairs to classify at least the portion as either speech or non-speech.

2. A method as recited in claim 1, wherein the using comprises:

generating an input Gaussian Model corresponding to the plurality of frames based on the extracted line spectrum pairs;

comparing the input Gaussian Model to a Vector Quantization codebook including a plurality of trained Gaussian Models;

identifying one of the plurality of trained Gaussian Models that is closest to the input Gaussian Model;

determining a distance between the input Gaussian Model and the closest trained Gaussian Model; and

classifying at least the portion as speech if the distance is less than a threshold value.

3. A method as recited in claim 1, wherein the using comprises:

generating an input Gaussian Model corresponding to the plurality of frames based on the extracted line spectrum pairs;

identifying one of the plurality of trained Gaussian Models that is closest to the input Gaussian Model;

1 determining a distance between the input Gaussian Model and the closest
2 trained Gaussian Model; and
3 classifying at least the portion as non-speech if the distance is greater than a
4 first threshold value.

5
6 **4.** A method as recited in claim 3, further comprising:
7 determining an energy distribution of the plurality of frames in a first
8 bandwidth; and
9 classifying at least the portion as non-speech if the distance is greater than a
10 second threshold value and the energy distribution of the plurality of frames in the
11 first bandwidth is less than a third threshold value, wherein the second threshold
12 value is less than the first threshold value.

13
14 **5.** A method as recited in claim 4, further comprising:
15 determining an energy distribution of the plurality of frames in a second
16 bandwidth; and
17 classifying at least the portion as speech if the distance is less than the
18 second threshold value and the energy distribution of the plurality of frames in the
19 second bandwidth is greater than a fourth threshold value.

20
21 **6.** A method as recited in claim 5, further comprising otherwise
22 classifying at least the portion as speech.
23
24
25

1 7. A method as recited in claim 2, further comprising:
2 extracting a high zero crossing rate ratio feature from the plurality of
3 frames;
4 extracting a low short time energy ratio feature from the plurality of frames;
5 extracting a spectrum flux feature from the plurality of frames;
6 pre-classifying the portion as speech or non-speech based at least in part on
7 an average zero crossing rate, the high zero crossing rate ratio, the low short time
8 energy ratio, and the spectrum flux features;
9 using a first value as the threshold value if the portion is pre-classified as
10 speech; and
11 using a second value as the threshold value if the portion is pre-classified as
12 non-speech, wherein the second value is greater than the first value.

13
14 8. One or more computer-readable memories containing a computer
15 program that is executable by a processor to perform the method recited in claim
16 1.

17
18 9. A method comprising:
19 separating at least a portion of an audio signal into a plurality of frames;
20 extracting a periodicity feature from the plurality of frames; and
21 using at least the periodicity feature to classify at least the portion as either
22 music or environment sound.

1 **10.** A method as recited in claim 9, wherein the periodicity feature
2 comprises a noise frame ratio that identifies a ratio of noise frames to non-noise
3 frames in the plurality of frames.

4
5 **11.** A method as recited in claim 10, further comprising classifying at
6 least the portion as environment sound if the noise frame ratio exceeds a threshold
7 value.

8
9 **12.** A method as recited in claim 10, further comprising:
10 extracting, from the plurality of frames, a band periodicity for each of a
11 plurality of bands of the audio signal and a full band periodicity that is a
12 concatenation of the band periodicities for each of the plurality of bands; and
13 classifying at least the portion as environment sound if the first band
14 periodicity is less than a first threshold or the second band is less than a second
15 threshold.

16
17 **13.** A method as recited in claim 9, wherein the periodicity feature
18 comprises a band periodicity for each of a plurality of bands of the audio signal.

19
20 **14.** A method as recited in claim 13, further comprising:
21 extracting a full band periodicity from the plurality of frames that is a
22 concatenation of the band periodicities for each of the plurality of bands; and
23 classifying at least the portion as environment sound if the full band
24 periodicity exceeds a threshold value.
25

1 **15.** A method as recited in claim 9, further comprising extracting a
2 spectrum flux feature from the plurality of frames, and wherein the using
3 comprises using at least the periodicity feature and the spectrum flux feature to
4 classify at least the portion as either music or environment sound.

5
6 **16.** A method as recited in claim 15, wherein the spectrum flux feature
7 is extracted by determining a Fast Fourier Transform for each of the plurality of
8 frames and calculating a difference in the Fast Fourier Transforms for successive
9 frames.

10
11 **17.** A method as recited in claim 15, further comprising:
12 extracting, from the plurality of frames, an energy distribution in a band of
13 the audio signal; and
14 classifying at least the portion as environment sound if the band energy
15 distribution is less than a first threshold or the spectrum flux exceeds a second
16 threshold.

17
18 **18.** A method as recited in claim 9, wherein the periodicity feature
19 comprises a band periodicity for each of a plurality of bands of the audio signal,
20 and further comprising:

21 extracting, from the plurality of frames, a spectrum flux feature;

22 extracting, from the plurality of frames, an energy feature indicating an
23 amount of energy in at least one band of the portion; and
24
25

1 classifying at least the portion as environment sound if the amount of
2 energy is less than a first threshold and the spectrum flux is less than a second
3 threshold.

4
5 **19.** One or more computer-readable memories containing a computer
6 program that is executable by a processor to perform the method recited in claim
7 9.

8
9 **20.** A method comprising:
10 separating at least a portion of an audio signal into a plurality of frames;
11 extracting a periodicity feature for each of the plurality of frames; and
12 using at least the periodicity feature to classify the plurality of frames as
13 either music with vocals or music without vocals.

14
15 **21.** A method as recited in claim 20, wherein the periodicity feature
16 comprises a band periodicity for each of a plurality of bands of the audio signal.

17
18 **22.** A method as recited in claim 21, further comprising classifying at
19 least the portion as music with vocals if the band periodicity of at least one of the
20 plurality of bands is greater than a first threshold and less than a second threshold.
21
22
23
24
25

1 **23.** A method as recited in claim 22, further comprising classifying at
2 least the portion as environment sound if the band periodicity of each of the
3 plurality of bands is less than the second threshold, and otherwise classifying at
4 least the portion as music without vocals.

5
6 **24.** One or more computer-readable memories containing a computer
7 program that is executable by a processor to perform the method recited in claim
8 20.

9
10 **25.** A method for determining when a speaker changes, the method
11 comprising:

12 separating at least a portion of an audio signal into a plurality of frames;

13 extracting line spectrum pairs from each of the plurality of frames; and

14 determining when a speaker of the audio signal changes based at least in
15 part on the line spectrum pairs.

16
17 **26.** A method as recited in claim 25, wherein the determining
18 comprises:

19 calculating a difference between line spectrum pairs for successive frames
20 of the plurality of frames;

21 if the difference between two line spectrum pairs exceeds a threshold value,
22 then determining that the speaker has changed, otherwise determining that the
23 speaker has not changed.

1 **27.** One or more computer-readable memories containing a computer
2 program that is executable by a processor to perform the method recited in claim
3 25.

4
5 **28.** An apparatus comprising:
6 a line spectrum pair (LSP) analyzer to extract line spectrum pairs from a
7 portion of an audio signal; and
8 a speech discriminator, communicatively coupled to the LSP analyzer, to
9 classify the portion of the audio signal as either speech or non-speech based at
10 least in part on the LSP analyzer.

11
12 **29.** An apparatus as recited in claim 28, further comprising:
13 a distance calculator, communicatively coupled to the LSP analyzer, to
14 determine a distance between at least one of the trained Gaussian Models and an
15 input Gaussian Model based on the extracted line spectrum pairs; and
16 wherein the speech discriminator is further to classify the portion of the
17 audio signal as either speech or non-speech based at least in part on the distance
18 between the at least one of the trained Gaussian Models and the input Gaussian
19 Model.

20
21 **30.** An apparatus as recited in claim 28, further comprising:
22 a Fast Fourier Transform (FFT) analyzer to extract Fast Fourier Transform
23 features from the portion of the audio signal;
24
25

1 an energy distribution calculator, communicatively coupled to both the FFT
2 analyzer and the speech discriminator, to determine an energy distribution of the
3 portion of the audio signal in at least one bandwidth; and

4 wherein the speech discriminator is further to classify the portion of the
5 audio signal as either speech or non-speech based at least in part on the energy
6 distribution of the portion of the audio signal in the at least one bandwidth.

7
8 **31.** An apparatus comprising:

9 a band periodicity calculator to determine a periodicity of each of a
10 plurality of bands of a portion of an audio signal; and

11 a discriminator, communicatively coupled to the band periodicity
12 calculator, to classify the portion of the audio signal as music or environment
13 sound based at least in part on the periodicity of one of the plurality of bands.

14
15 **32.** An apparatus as recited in claim 31, further comprising:

16 a noise frame ratio calculator, communicatively coupled to the
17 discriminator, to determine a noise frame ratio of the portion of the audio signal;
18 and

19 wherein the discriminator is to classify the portion of the audio signal as
20 music or environment sound based at least in part on the periodicity of one of the
21 plurality of bands and on the noise frame ratio of the portion.

22
23 **33.** An apparatus as recited in claim 31, further comprising:

24 a spectrum flux analyzer, communicatively coupled to the discriminator, to
25 determine a spectrum flux of the portion of the audio signal; and

1 wherein the discriminator is to classify the portion of the audio signal as
2 music or environment sound based at least in part on the periodicity of one of the
3 plurality of bands and on the spectrum flux of the portion.

4
5 **34.** A method comprising:
6 receiving an audio signal;
7 separating the audio signal into a plurality of portions; and
8 classifying each of the plurality of portions, based at least in part on
9 periodicity features of the portion, as one of: speech, music, silence, and
10 environment sound.

11
12 **35.** A method as recited in claim 34, wherein the periodicity features
13 include a noise frame ratio that identifies a ratio of noise frames to non-noise
14 frames in the plurality of frames.

15
16 **36.** A method as recited in claim 35, wherein the classifying comprises
17 classifying at least the portion as environment sound if the noise frame ratio
18 exceeds a threshold value.

19
20 **37.** A method as recited in claim 34, further comprising:
21 extracting, from the plurality of frames, a band periodicity for each of a
22 plurality of bands of the audio signal and a full band periodicity that is a
23 concatenation of the band periodicities for each of the plurality of bands; and
24 wherein the classifying comprises classifying at least the portion as
25 environment sound if a band periodicity of a first of the plurality of bands is less

1 than the first threshold a band periodicity of a second of the plurality of bands is
2 less than the second threshold. .
3

4 **38.** A method as recited in claim 34, wherein the periodicity features
5 include a band periodicity for each of a plurality of bands of the audio signal.
6

7 **39.** A method as recited in claim 38, further comprising:
8 extracting a full band periodicity from the plurality of frames that is a
9 concatenation of the band periodicities for each of the plurality of bands; and
10 wherein the classifying comprises classifying at least the portion as
11 environment sound if the full band periodicity exceeds a threshold value.
12

13 **40.** A method as recited in claim 34, further comprising:
14 extracting a spectrum flux feature from the plurality of frames; and
15 wherein the classifying comprises classifying at least the portion as either
16 music or environment sound based at least in part on the periodicity feature and
17 the spectrum flux feature.
18

19 **41.** A method as recited in claim 34, further comprising:
20 extracting line spectrum pairs from each of the plurality of frames;
21 generating an input Gaussian Model corresponding to the plurality of
22 frames based on the extracted line spectrum pairs;
23 comparing the input Gaussian Model to a Vector Quantization codebook
24 including a plurality of trained Gaussian Models;
25

1 identifying one of the plurality of trained Gaussian Models that is closest to
2 the input Gaussian Model;
3 determining a distance between the input Gaussian Model and the closest
4 trained Gaussian Model; and
5 classifying at least the portion as speech if the distance is less than a
6 threshold value.

7
8 **42.** A method as recited in claim 34, further comprising:
9 extracting line spectrum pairs from each of the plurality of frames;
10 generating an input Gaussian Model corresponding to the plurality of
11 frames based on the extracted line spectrum pairs;
12 identifying one of the plurality of trained Gaussian Models that is closest to
13 the input Gaussian Model;
14 determining a distance between the input Gaussian Model and the closest
15 trained Gaussian Model; and
16 classifying at least the portion as one of music, silence, or environment
17 sound if the distance is greater than a first threshold value.

18
19 **43.** A method as recited in claim 42, further comprising:
20 determining an energy distribution of the plurality of frames in a first
21 bandwidth; and
22 classifying at least the portion as one of music, silence, or environment
23 sound if the distance is greater than a second threshold value and the energy
24 distribution of the plurality of frames in the first bandwidth is less than a third
25

1 threshold value, wherein the second threshold value is less than the first threshold
2 value.

3 44. A method as recited in claim 43, further comprising:
4 determining an energy distribution of the plurality of frames in a second
5 bandwidth; and

6 classifying at least the portion as one of music, silence, or environment
7 sound if the distance is greater than a fourth threshold value and the energy
8 distribution of the plurality of frames in the second bandwidth is less than a fifth
9 threshold value, wherein the fourth threshold value is less than the first threshold
10 value.

11
12 45. A method as recited in claim 44, further comprising otherwise
13 classifying at least the portion as speech.

14
15 46. One or more computer-readable memories containing a computer
16 program that is executable by a processor to perform the method recited in claim
17 34.

18
19 47. One or more computer-readable media having stored thereon a
20 computer program to classify a portion of an audio signal as speech, music,
21 silence, or environment sound, wherein the computer program, when executed by
22 one or more processors, causes the one or more processors to perform acts
23 including:

24 (a) analyzing line spectrum pair features of the portion to determine if
25 the portion is speech;

1 (b) analyzing energy features of the portion to determine if the portion is
2 silence;

3 (c) analyzing periodicity features of the portion to determine if the
4 portion is music or environment sound; and

5 (d) classifying the portion as speech, music, silence, or environment
6 sound based on at least one of the analyzing acts (a)-(c).
7

8 **48.** One or more computer-readable media as recited in claim 47,
9 wherein the computer program is further to cause the one or more processors to
10 perform the acts (a) – (d) in the order (a), then (b), then (c), then (d).
11

12 **49.** One or more computer-readable media as recited in claim 48,
13 wherein the computer program is further to cause the one or more processors to
14 perform act (b) only if act (a) results in a determination that the portion is not
15 speech.
16

17 **50.** One or more computer-readable media as recited in claim 48,
18 wherein the computer program is further to cause the one or more processors to
19 perform act (c) only if act (b) results in a determination that the portion is not
20 silence.
21
22
23
24
25

1 **ABSTRACT**

2 A portion of an audio signal is separated into multiple frames from which
3 one or more different features are extracted. These different features are used, in
4 combination with a set of rules, to classify the portion of the audio signal into one
5 of multiple different classifications (for example, speech, non-speech, music,
6 environment sound, silence, etc.). In one embodiment, these different features
7 include one or more of line spectrum pairs (LSPs), a noise frame ratio, periodicity
8 of particular bands, spectrum flux features, and energy distribution in one or more
9 of the bands. The line spectrum pairs are also optionally used to segment the
10 audio signal, identifying audio classification changes as well as speaker changes
11 when the audio signal is speech.
12
13
14
15
16
17
18
19
20
21
22
23
24
25





Fig. 1






Fig. 3




Fig. 4




Fig. 5

1 **IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

2 InventorshipJiang et al.
3 Applicant Microsoft Corporation
4 Attorney's Docket No. MS1-442US
5 Title: Improved Audio Segmentation and Classification

6 **DECLARATION FOR PATENT APPLICATION**

7 As a below named inventor, I hereby declare that:

8 My residence, post office address and citizenship are as stated below next to
9 my name.

10 I believe I am the original, first and sole inventor (if only one name is listed
11 below) or an original, first and joint inventor (if plural names are listed below) of the
12 subject matter which is claimed and for which a patent is sought on the invention
13 entitled "Improved Audio Segmentation and Classification," the specification of
14 which is attached hereto.

15 I have reviewed and understand the content of the above-identified
16 specification, including the claims.

17 I acknowledge the duty to disclose information which is material to the
18 examination of this application in accordance with Title 37, Code of Federal
19 Regulations, § 1.56(a).

20 PRIOR FOREIGN APPLICATIONS: no applications for foreign patents or
21 inventor's certificates have been filed prior to the date of execution of this
22 declaration.

23 **Power of Attorney**

24 I appoint the following attorneys to prosecute this application and transact all
25 future business in the Patent and Trademark Office connected with this application:
26 Lewis C. Lee, Reg. No. 34,656; Daniel L. Hayes, Reg. No. 34,618; Allan T.

1 Sponseller, Reg. 38,318; Steven R. Sponseller, Reg. No. 39,384; James R.
2 Banowsky, Reg. No. 37,773; Lance R. Sadler, Reg. No. 38,605; Michael A. Proksch,
3 Reg. No. 43,021; Thomas A. Jolly, Reg. No. 39,241; David A. Morasch, Reg. No.
4 42,905; Kasey C. Christie, Reg. No. 40,559; Katie E. Sako, Reg. No. 32,628 and
5 Daniel D. Crouse, Reg. No. 32,022.

6 Send correspondence to: LEE & HAYES, PLLC, 421 W. Riverside Avenue,
7 Suite 500, Spokane, Washington, 99201. Direct telephone calls to: Allan T.
8 Sponseller (509) 324-9256.

9
10 All statements made herein of my own knowledge are true and that all
11 statements made on information and belief are believed to be true; and further that
12 these statements were made with the knowledge that willful false statements and the
13 like so made are punishable by fine or imprisonment, or both, under Section 1001 of
14 Title 18 of the United States Code and that such willful false statement may
15 jeopardize the validity of the application or any patent issued therefrom.

16
17 * * * * *

18 Full name of inventor: Hao Jiang

19 Inventor's Signature Hao Jiang Date: April 06, 2000

20 Residence: Beijing, China


21 Citizenship: China

22 Post Office Address: 5F, Beijing Sigma Center
23 49 Zhichun Road
24 Haidan District
25 Beijing, China 100080

Full name of inventor:

Hongjiang Zhang

Inventor's Signature



Date: April 06, 2000

Residence:

Beijing, China

Citizenship:

China

Post Office Address:

2741 Capital Paradise
Shun Yi District
Beijing, China 101300